

--- LWIR Continuous zoom – commercial off the shelf lens

KEW

LWIR 25 – 225 mm Continuous zoom
 Lens with DSP controller for 640x480x17 μ detectors



FEATURES / APPLICATIONS / CAPABILITIES

- The ultimate lens for medium to long range surveillance systems in various applications.
- Excellent MTF performances
- Optimized for relatively short total track and low weight

PARAMETER		VALUE	NOTES
Main	Sub		
OPTICAL			
Focal Length / F#		25-225 mm / F1.5	Nominal values. F# constant for all zoom range
Detector (FPA) type / size		640 x 480 pixels x 17 microns	Smaller detectors size are also supported
FOV (degrees)		Wide FOV: 24.3°(H) x 18.6° (V) Narrow FOV: 2.8° (H) x 2.1° (V)	For detector size of 10.88 x 8.16 mm (640 x 480 x 17 μ) – All to within \pm 7%
Optical Coatings			
	All internal surfaces	High efficiency AR coating	Average transmission: ~80%
	Front surface	High durability AR coating	DLC is available upon request
Optical Total lens track		220 mm	Nominal, From 1 st lens vertex to FPA
Optical Back Focal Length		~20 mm	Nominal, From last lens vertex to FPA
MECHANICAL			
Mechanical Back Focal Length		17.6 mm	Nominal
Focus / Zoom mechanism		Motorized	Focus range: 5m - infinity
Total Weight		~3000 grams	Nominal (Front element is sealed)
External Dimensions		Max Diameter: 179 mm; Length: 210 mm	
ELECTRICAL			
Power Input		12VDC, 1.0A	Nominal
Communication Protocol		RS-422/232 Full Duplex	Baud rate 19,200, n, 8, 1
ENVIRONMENTAL			
Operating/Storage Temperature		-32°C to +55°C / -40°C to +70°C	
Shock and Vibrations		Per applicable standard	
Front lens sealing		IP67	By request

